

ATTIVA 6L.6



ITALCAR INDUSTRIAL SRL | Via Bruino, 36 | 10040 Rivalta di Torino (TO) Tel. +39 011 9040225 | Fax +39 011 9032986 | info@italcar.com | www.italcar.com 48 VOLT WITH AC SYSTEM 8 x 6V LEAD-ACID BATTERIES 205/50-10 ALUMINUM RIMS FRONT & REAR LED LIGHTS HYDRAULIC BRAKES ON 4

HYDRAULIC BRAKES ON 4 WHEELS + HANDBRAKE









ATTIVA 6L.6

places:	6 (4+2)
batteries:	8 x 6V, US2200 standard
motor:	AC 48V – Mahle Letrika
controller:	sevcon GEN4 – AC – 450A
transmission:	rear axle, 19 spline, ratio 16:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	30 km/h
range	80 km
max hill climbing ability	25% (then 14°)
vehicle dimensions:	
overall	3700mm x 1200mm x 1800mm
ground clearance (empty):	210mm
turning radius (min):	4 mt
wheel base	2400mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel
front	disc
rear	drum
tyres: recommended pressure:	205 / 50 – 10 with aluminium rims 1,7 bar (25psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	Includes: reverse buzzer; digital speedometer, front and rear LED lights, horn, direction indicators, rear-view mirrors, one piece plexiglass

all above specification were correct at the time of the publishing and are indicatives and not binding. ITALCAR INDUSTRIAL Srl maintains the right to bring any changes without notice



seguici su - follow us on



clicca mi piace - like us on

